



Светильник линейный архитектурный AL-16100-2 RGB (16 pix) DC12V/12W 48шт x SMD5050/IP65

Артикул AL-16100-2 RGB (16 pix)

В наличии

2 шт.

Склад Красноярск

1 шт.

Склад Кемерово

1 шт.

Характеристики

Производитель SignImpress



LED linear light

AL-16100

- High quality aluminum shell, surface anodic oxidation process, bright but light yellow.
- Improved light source design, long lifespan, high luminous efficiency.
- High quality and high thermal conductivity alloy PCB with excellent thermal conductivity and high temperature coefficient.
- Mid-high white PC lens covers with light scattering treatment.
- Private control can be achieved by DMX512 Technology.

RoHS CE ENEC



Product specification


Basic parameters		Optical parameters	
Color Temperature	Warm white 3000K/4000K	Beam diameter (mm)	1610mm
Rated power	12W/12W	CRI	80
Led module	30-30	Luminous efficiency	45-170lm/W
Led light source	SMD 5050	Application parameters	
Rated voltage	DC12V	Mounting mode	IP65
Dim	Bluetooth, DMX512	Working mode	40%-100%
Anti-plasma ballast	300	Working temperature	-10°C-35°C
Life span	100,000	Weight	150g
Material	PC	Transmission	90%
Power supply	1000mA	Dimensional parameters	
Control method	remote control / DMX512 / APP	Height	12mm
Beam	1:1.4	Mounting distance	800mm standard distance
Mechanical parameters		Color material	PC
Material	ALUMINUM	Length	1610mm
Beam diameter	1610mm	Width	27mm
Weight	150g	Height	12mm
Transmission	90%		
Control type	DMX		

Note: Refer to the data on the back of the LED chip for more information. Please refer to the technical manual.

DIMENSION



LIGHT DISTRIBUTION CURVE



INSTALLATION METHOD

